

Kaba EF-Flash 780

Electronic Door Lock

The Kaba Electronic Door Solution E-Flash Series



Kaba E-Flash Biometrics Electronic Door Lock E-780

Features

User friendly access features







ngerprint Access Pincoo

Pincode Access

Mechanical Key Override

Security at its best







Free Access or Privacy Mode

Effortless Programming

- enhanced security with scramble code capability for pincode access
- Standard or double security access selection mode
- Fingerprint mark free touch pad
- Easy registration and programming
- **◆** Voice guided instructions
- Voice guide volume control
- Secure and power saving european lockcase
- Anti-panic system on exit
- 🔊 Anti break-in and damage alarm
- Wrong try lock out delay
- External 9V battery terminal for emergency use
- 1 Left / Right handle installation
- Remote Control (Optional)



Specifications		
Access	Biometrics Capacity	Up to 100 fingerprint registrations
	Pincode	4 digit - 12 digit combination
Dimension (Excluding Handle)	External Body	23.5D x 74W x 282H (mm)
	Internal Body	25.0D x 74w x 282H (mm)
Dimension (Including Handle)	External Body	78.0D x 151W x 282H (mm)
	Internal Body	79.5D x 151W x 282H (mm)
Door Thickness	32mm x 65mm	
Lockset Backset	55mm / 70mm	
Material	Zinc Die Casting	
Color	White-Chrome / Black-Chrome	
Operating Temperature	15 ~ 55 degrees	
Power Supply	4 x 1.5V AA Alkaline Batteries	
Battery Life	Approx 1 Year, 10 openings a day	
IP Rating	IP54	

^{*} Battery lifespan is dependent on ambient temperature, humidity, frequency of usage and quality of batteries

^{**}Product specification is subjected to changes without prior notice in view of product improvement





Certified Management-System ISO 9001, Reg.-No. 14572

Subject to technical changes

® = registered Trademark of Kaba AG, Wetzikon (Switzerland)



Kaba Security Pte Ltd Block 203A, #07-03 Hemderson Road Henderson Industrial Building Singapore 159546 Tel. +65 6275 1211 Fax. + 65 6275 1233 info@kaba.com.sg

www.kaba.com.sg